LISTING OF THE CLAIMS

1. (original): An automobile model comprising:

a pair of left and right driven wheels which are independently driven by different driving

sources;

a pair of left and right steered wheels; and

a steered wheel-supporting mechanism which supports the steered wheels such that each

steered wheel is adapted to turn around a predetermined steering axis and such that the steered

wheels are adapted to turn in the same direction in association with each other,

wherein the steering axis is inclined with respect to a vertical direction such that an upper

portion of the steering axis is located rearward of a lower portion of the steering axis in a

traveling direction.

2. (original): The automobile model according to claim 1, wherein an inclination angle

of the steering axis with respect to the vertical direction is set in a range of 20° to 40°.

3. (original): The automobile model according to claim 1, wherein the steered wheel-

supporting mechanism supports the steered wheels such that center lines of the steered wheels as

viewed from directly above in a straight-ahead driving state are inclined with respect to the

traveling direction.

4. (original): The automobile model according to claim 1, wherein the steered wheel-

supporting mechanism supports the steered wheels such that center lines of the steered wheel as

Application No. 10/511,919 3 Docket No.: 9867/0201967-US0

Amendment dated May 22, 2007 Reply to Office Action of January 30, 2007

viewed from front in the traveling direction in a straight-ahead driving state are inclined with

respect to the vertical direction.

5. (original): The automobile model according to claim 1, wherein the steered wheel-

supporting mechanism supports the steered wheels such that the left and right steered wheels are

adapted to incline in the same direction in association with each other as viewed from front in the

traveling direction.

6. (original): The automobile model according to claim 3, wherein the steered wheel-

supporting mechanism supports the steered wheels such that center lines of the steered wheel as

viewed from front in the traveling direction in a straight-ahead driving state are inclined with

respect to the vertical direction.

7. (original): The automobile model according to claim 6, wherein the steered wheel-

supporting mechanism supports the steered wheels such that the left and right steered wheels can

incline in the same direction in association with each other as viewed from front in the traveling

direction.